

Pag.

T-62A AA

1

*SUCTION & DELIVERY**EXTRA HEAVY DUTY**SUBMARINE HOSE FOR C.A.L.M**AND C.M.B.M APPLICATIONS**15 BAR (225 PSI)**OCIMF (Fourth Edition - 1991)*

T-62B AA

2

*SUCTION & DELIVERY**EXTRA HEAVY DUTY**SUBMARINE HOSE FOR C.A.L.M**AND C.M.B.M APPLICATIONS**WITH BUILT IN COLLARS**FOR RETENTION FLOATS**15 BAR (225 PSI)**OCIMF (Fourth Edition - 1991)*

T-62C AA

3

*SUCTION & DELIVERY**EXTRA HEAVY DUTY**SUBMARINE HOSE**FOR C.A.L.M AND**C.M.B.M APPLICATIONS**ONE END REINFORCED**15 BAR (225 PSI)**OCIMF (Fourth Edition - 1991)*

T-62D AA

4

*SUCTION & DELIVERY**EXTRA HEAVY DUTY**SUBMARINE HOSE FOR C.A.L.M**AND C.M.B.M APPLICATIONS**BOTH ENDS REINFORCED**15 BAR (225 PSI)**OCIMF (Fourth Edition - 1991)*

T-62E AA

5

*SUCTION & DELIVERY**EXTRA HEAVY DUTY**SUBMARINE HOSE FOR C.A.L.M**AND C.M.B.M APPLICATIONS**TANKER RAIL CONNECTION**15 BAR (225 PSI)**OCIMF (Fourth Edition - 1991)*

T-63A AA

6

*SUCTION & DELIVERY**EXTRA HEAVY DUTY**FLOATING HOSE**FOR MOORING APPLICATIONS**15 BAR (225 PSI)**OCIMF (Fourth Edition - 1991)*

T-63B AA

7

*SUCTION & DELIVERY**EXTRA HEAVY DUTY**FLOATING HOSE**FOR MOORING APPLICATIONS**ONE END REINFORCED**15 BAR (225 PSI)**OCIMF (Fourth Edition - 1991)*

T-63C AA

8

*SUCTION & DELIVERY**EXTRA HEAVY DUTY**FLOATING HOSE**FOR MOORING APPLICATIONS**TANKER RAIL CONNECTION**15 BAR (225 PSI)**OCIMF (Fourth Edition - 1991)*

T-643 AA

9

*"FLOWLINE E RISER" DI PETROLIO**GREGGIO 25 BAR*

T-62A AA
SUCTION & DELIVERY
EXTRA HEAVY DUTY
SUBMARINE HOSE FOR C.A.L.M
AND C.M.B.M APPLICATIONS
15 BAR (225 PSI)
OCIMF (Fourth Edition - 1991)



TUBE	BLACK NBR - FUEL AND OIL RESISTANT
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
COVER	BLACK CR - ABRASION, OZONE, SALT WATER AND HYDROCARBON RESISTANT
APPLICATION	FUEL AND OIL TRANSFER WITH UP TO 55% MAX AROMATIC CONTENT IN OFF SHORE APPLICATIONS
TEMPERATURE	-20°C +82°C (-4°F +180°F)
LENGTHS	* 9,1 / 10,7 m (30/35 FEET)
END FITTINGS	BUILT-IN FLANGED NIPPLES SCREWED ON CUSTOMER REQUIREMENT
ELECTRICALLY	CONTINUOUS. DISCONTINUOUS ON CUSTOMER REQUIREMENT
SAFETY FACTOR	5:1
TEMPORARY	<=1.5% AT 15 BAR (225 PSI)
ELONGATION AT	
FACTORY TEST	
PRESSURE	
PERMANENT	<= 0.5% AFTER HYDROSTATIC TEST
ELONGATION	
TOLERANCES ON	+2/-1%
LENGTH	
BRAND TEXT	ACCORDING TO OCIMF (Fourth Edition - 1991)
BRAND TYPE	WHITE LETTERS
PACKING	PE FILM + FLANGE OR NIPPLE PROTECTION SPECIAL PACKING ON CUSTOMER REQUIREMENT
APPROVALS	

ID	ID	Nominal Weight	WP	WP	Vac.	BR mm	Available
mm	inch	Kg/m	bar	psi	%		Length
150	6		15	225	100	600	* 9,1 / 10,7 m - 30/35 ft
200	8		15	225	100	800	* 9,1 / 10,7 m - 30/35 ft
250	10		15	225	100	1000	* 9,1 / 10,7 m - 30/35 ft
300	12		15	225	100	1200	* 9,1 / 10,7 m - 30/35 ft

T-62B AA
SUCTION & DELIVERY
EXTRA HEAVY DUTY
SUBMARINE HOSE FOR C.A.L.M
AND C.M.B.M APPLICATIONS
WITH BUILT IN COLLARS
FOR RETENTION FLOATS
15 BAR (225 PSI)
OCIMF (Fourth Edition - 1991)



TUBE	BLACK NBR - FUEL AND OIL RESISTANT
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
COVER	BLACK CR - ABRASION, OZONE, SALT WATER AND HYDROCARBON RESISTANT
APPLICATION	FUEL AND OIL TRANSFER WITH UP TO 55% MAX AROMATIC CONTENT IN OFF SHORE APPLICATIONS
TEMPERATURE	-20°C +82°C (-4°F +180°F)
LENGTHS	* 9,1 / 10,7 m (30/35 FEET)
END FITTINGS	BUILT-IN FLANGED NIPPLES SCREWED ON CUSTOMER REQUIREMENT
ELECTRICALLY	CONTINUOUS. DISCONTINUOUS ON CUSTOMER REQUIREMENT
SAFETY FACTOR	5:1
TEMPORARY	<=1.5% AT 15 BAR (225 PSI)
ELONGATION AT	
FACTORY TEST	
PRESSURE	
PERMANENT	<=0.5 AFTER HYDROSTATIC TEST
ELONGATION	
TOLERANCES ON	+2/-1%
LENGTH	
BRAND TEXT	ACCORDING TO OCIMF (Fourth Edition - 1991)
BRAND TYPE	WHITE LETTERS
PACKING	PE FILM + FLANGE OR NIPPLE PROTECTION SPECIAL PACKING ON CUSTOMER REQUIREMENT

APPROVALS

ID mm	ID inch	Nominal Weight Kg/m	WP bar	WP psi	Vac. %	BR mm	Available Length
150	6		15	225	100	600	* 9,1 / 10,7 m - 30/35 ft
200	8		15	225	100	800	* 9,1 / 10,7 m - 30/35 ft
250	10		15	225	100	1000	* 9,1 / 10,7 m - 30/35 ft
300	12		15	225	100	1200	* 9,1 / 10,7 m - 30/35 ft

T-62C AA
SUCTION & DELIVERY
EXTRA HEAVY DUTY
SUBMARINE HOSE
FOR C.A.L.M AND
C.M.B.M APPLICATIONS
ONE END REINFORCED
15 BAR (225 PSI)
OCIMF (Fourth Edition - 1991)



TUBE	BLACK NBR - FUEL AND OIL RESISTANT
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
COVER	BLACK CR - ABRASION, OZONE, SALT WATER AND HYDROCARBON RESISTANT
APPLICATION	FUEL AND OIL TRANSFER WITH UP TO 55% MAX AROMATIC CONTENT IN OFF SHORE APPLICATIONS
TEMPERATURE	-20°C +82°C (-4°F +180°F)
LENGTHS	* 9,1 / 10,7 m (30/35 FEET)
END FITTINGS	BUILT-IN FLANGED NIPPLES SCREWED ON CUSTOMER REQUIREMENT
ELECTRICALLY	CONTINUOUS. DISCONTINUOUS ON CUSTOMER REQUIREMENT
SAFETY FACTOR	5:1
TEMPORARY	<=1.5% AT 15 BAR (225 PSI)
ELONGATION AT	
FACTORY TEST	
PRESSURE	
PERMANENT	<=0.5 AFTER HYDROSTATIC TEST
ELONGATION	
TOLERANCES ON	+2/-1%
LENGTH	
BRAND TEXT	ACCORDING TO OCIMF (Fourth Edition - 1991)
BRAND TYPE	WHITE LETTERS
PACKING	PE FILM + FLANGE OR NIPPLE PROTECTION SPECIAL PACKING ON CUSTOMER REQUIREMENT

APPROVALS

ID mm	ID inch	Nominal Weight Kg/m	WP bar	WP psi	Vac. %	BR mm	Available Length
150	6		15	225	100	600	* 9,1 / 10,7 m - 30/35 FEET
200	8		15	225	100	800	* 9,1 / 10,7 m - 30/35 FEET
250	10		15	225	100	1000	* 9,1 / 10,7 m - 30/35 FEET
300	12		15	225	100	1200	* 9,1 / 10,7 m - 30/35 FEET

T-62D AA
SUCTION & DELIVERY
EXTRA HEAVY DUTY
SUBMARINE HOSE FOR C.A.L.M
AND C.M.B.M APPLICATIONS
BOTH ENDS REINFORCED
15 BAR (225 PSI)
OCIMF (Fourth Edition - 1991)



TUBE	BLACK NBR - FUEL AND OIL RESISTANT
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
COVER	BLACK CR - ABRASION, OZONE, SALT WATER AND HYDROCARBON RESISTANT
APPLICATION	FUEL AND OIL TRANSFER WITH UP TO 55% MAX AROMATIC CONTENT IN OFF SHORE APPLICATIONS
TEMPERATURE	-20°C +82°C (-4°F +180°F)
LENGTHS	* 9,1 / 10,7 m (30/35 FEET)
END FITTINGS	BUILT-IN FLANGED NIPPLES SCREWED ON CUSTOMER REQUIREMENT
ELECTRICALLY	CONTINUOUS. DISCONTINUOUS ON CUSTOMER REQUIREMENT
SAFETY FACTOR	5:1
TEMPORARY	<=1.5% AT 15 BAR (225 PSI)
ELONGATION AT	
FACTORY TEST	
PRESSURE	
PERMANENT	<=0.5 AFTER HYDROSTATIC TEST
ELONGATION	
TOLERANCES ON	+2/-1%
LENGTH	
BRAND TEXT	ACCORDING TO OCIMF (Fourth Edition - 1991)
BRAND TYPE	WHITE LETTERS
PACKING	PE FILM + FLANGE OR NIPPLE PROTECTION SPECIAL PACKING ON CUSTOMER REQUIREMENT

APPROVALS

ID mm	ID inch	Nominal Weight Kg/m	WP bar	WP psi	Vac. %	BR mm	Available Length
150	6		15	225	100	600	* 9,1 / 10,7 m - 30/35 FEET
200	8		15	225	100	800	* 9,1 / 10,7 m - 30/35 FEET
250	10		15	225	100	1000	* 9,1 / 10,7 m - 30/35 FEET
300	12		15	225	100	1200	* 9,1 / 10,7 m - 30/35 FEET

T-62E AA
SUCTION & DELIVERY
EXTRA HEAVY DUTY
SUBMARINE HOSE FOR C.A.L.M
AND C.M.B.M APPLICATIONS
TANKER RAIL CONNECTION
15 BAR (225 PSI)
OCIMF (Fourth Edition - 1991)



TUBE	BLACK NBR - FUEL AND OIL RESISTANT
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
COVER	BLACK CR - ABRASION, OZONE, SALT WATER AND HYDROCARBON RESISTANT
APPLICATION	FUEL AND OIL TRANSFER WITH UP TO 55% MAX AROMATIC CONTENT IN OFF SHORE APPLICATIONS
TEMPERATURE	-20°C +82°C (-4°F +180°F)
LENGTHS	* 9,1 / 10,7 m (30/35 FEET)
END FITTINGS	BUILT-IN FLANGED NIPPLES SCREWED ON CUSTOMER REQUIREMENT
ELECTRICALLY	CONTINUOUS. DISCONTINUOUS ON CUSTOMER REQUIREMENT
SAFETY FACTOR	5:1
TEMPORARY	<=1.5% AT 15 BAR (225 PSI)
ELONGATION AT	
FACTORY TEST	
PRESSURE	
PERMANENT	<=0.5 AFTER HYDROSTATIC TEST
ELONGATION	
TOLERANCES ON	+2/-1%
LENGTH	
BRAND TEXT	ACCORDING TO OCIMF (Fourth Edition - 1991)
BRAND TYPE	WHITE LETTERS
PACKING	PE FILM + FLANGE OR NIPPLE PROTECTION SPECIAL PACKING ON CUSTOMER REQUIREMENT

APPROVALS

ID mm	ID inch	Nominal Weight Kg/m	WP bar	WP psi	Vac. %	BR mm	Available Length
150	6		15	225	100	600	* 9,1 / 10,7 m - 30/35 FEET
200	8		15	225	100	800	* 9,1 / 10,7 m - 30/35 FEET
250	10		15	225	100	1000	* 9,1 / 10,7 m - 30/35 FEET
300	12		15	225	100	1200	* 9,1 / 10,7 m - 30/35 FEET

T-63A AA
SUCTION & DELIVERY
EXTRA HEAVY DUTY
FLOATING HOSE
FOR MOORING APPLICATIONS
15 BAR (225 PSI)
OCIMF (Fourth Edition - 1991)



TUBE	BLACK NBR - FUEL AND OIL RESISTANT
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
COVER	BLACK CR - ABRASION, OZONE, SALT WATER AND HYDROCARBON RESISTANT
APPLICATION	FUEL AND OIL TRANSFER WITH UP TO 55% MAX AROMATIC CONTENT IN OFF SHORE APPLICATIONS
TEMPERATURE	-20°C +82°C (-4°F +180°F)
LENGTHS	* 9,1 / 10,7 m (30/35 FEET)
END FITTINGS	BUILT-IN FLANGED NIPPLES SCREWED ON CUSTOMER REQUIREMENT
ELECTRICALLY	CONTINUOUS. DISCONTINUOUS ON CUSTOMER REQUIREMENT
SAFETY FACTOR	5:1
TEMPORARY	<=1.5% AT 15 BAR (225 PSI)
ELONGATION AT	
FACTORY TEST	
PRESSURE	
PERMANENT	<=0.5 AFTER HYDROSTATIC TEST
ELONGATION	
BRAND TEXT	ACCORDING TO OCIMF (Fourth Edition - 1991)
BRAND TYPE	WHITE LETTERS
PACKING	PE FILM + FLANGE OR NIPPLE PROTECTION SPECIAL PACKING ON CUSTOMER REQUIREMENT
APPROVALS	
TOLERANCES ON	+2/-1%
LENGTH	

ID	ID	Nominal Weight	WP	WP	Vac.	BR mm	Available
mm	inch	Kg/m	bar	psi	%		Length
150	6		15	225	100	600	* 9,1 / 10,7 m - 30/35 FEET
200	8		15	225	100	800	* 9,1 / 10,7 m - 30/35 FEET
250	10		15	225	100	1000	* 9,1 / 10,7 m - 30/35 FEET
300	12		15	225	100	1200	* 9,1 / 10,7 m - 30/35 FEET

T-63B AA
SUCTION & DELIVERY
EXTRA HEAVY DUTY
FLOATING HOSE
FOR MOORING APPLICATIONS
ONE END REINFORCED
15 BAR (225 PSI)
OCIMF (Fourth Edition - 1991)



TUBE	BLACK NBR - FUEL AND OIL RESISTANT
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
COVER	BLACK CR - ABRASION, OZONE, SALT WATER AND HYDROCARBON RESISTANT
APPLICATION	FUEL AND OIL TRANSFER WITH UP TO 55% MAX AROMATIC CONTENT IN OFF SHORE APPLICATIONS
TEMPERATURE	-20°C +82°C (-4°F +180°F)
LENGTHS	* 9,1 / 10,7 m (30/35 FEET)
END FITTINGS	BUILT-IN FLANGED NIPPLES SCREWED ON CUSTOMER REQUIREMENT
ELECTRICALLY	CONTINUOUS. DISCONTINUOUS ON CUSTOMER REQUIREMENT
SAFETY FACTOR	5:1
TEMPORARY	<=1.5% AT 15 BAR (225 PSI)
ELONGATION AT	
FACTORY TEST	
PRESSURE	
PERMANENT	<=0.5 AFTER HYDROSTATIC TEST
ELONGATION	
TOLERANCES ON	+2/-1%
LENGTH	
BRAND TEXT	ACCORDING TO OCIMF (Fourth Edition - 1991)
BRAND TYPE	WHITE LETTERS
PACKING	PE FILM + FLANGE OR NIPPLE PROTECTION SPECIAL PACKING ON CUSTOMER REQUIREMENT

APPROVALS

ID mm	ID inch	Nominal Weight Kg/m	WP bar	WP psi	Vac. %	BR mm	Available Length
150	6		15	225	100	600	* 9,1 / 10,7 m - 30/35 ft
200	8		15	225	100	800	* 9,1 / 10,7 m - 30/35 ft
250	10		15	225	100	1000	* 9,1 / 10,7 m - 30/35 ft
300	12		15	225	100	1200	* 9,1 / 10,7 m - 30/35 ft

T-63C AA
SUCTION & DELIVERY
EXTRA HEAVY DUTY
FLOATING HOSE
FOR MOORING APPLICATIONS
TANKER RAIL CONNECTION
15 BAR (225 PSI)
OCIMF (Fourth Edition - 1991)



TUBE	BLACK NBR - FUEL AND OIL RESISTANT
REINFORCEMENT	HIGH TENSILE TEXTILE CORDS WITH EMBEDDED STEEL HELIX WIRE
COVER	BLACK CR - ABRASION, OZONE, SALT WATER AND HYDROCARBON RESISTANT
APPLICATION	FUEL AND OIL TRANSFER WITH UP TO 55% MAX AROMATIC CONTENT IN OFF SHORE APPLICATIONS
TEMPERATURE	-20°C +82°C (-4°F +180°F)
LENGTHS	* 9,1 / 10,7 m (30/35 FEET)
END FITTINGS	BUILT-IN FLANGED NIPPLES SCREWED ON CUSTOMER REQUIREMENT
ELECTRICALLY	CONTINUOUS. DISCONTINUOUS ON CUSTOMER REQUIREMENT
SAFETY FACTOR	5:1
TEMPORARY	<=1.5% AT 15 BAR (225 PSI)
ELONGATION AT FACTORY TEST PRESSURE	
PERMANENT ELONGATION	<=0.5 AFTER HYDROSTATIC TEST
TOLERANCES ON LENGTH	+2/-1%
BRAND TEXT	ACCORDING TO OCIMF (Fourth Edition - 1991)
BRAND TYPE	WHITE LETTERS
PACKING	PE FILM + FLANGE OR NIPPLE PROTECTION SPECIAL PACKING ON CUSTOMER REQUIREMENT

APPROVALS

ID mm	ID inch	Nominal Weight Kg/m	WP bar	WP psi	Vac. %	BR mm	Available Length
150	6		15	225	100	600	* 9,1 / 10,7 m - 30/35 ft
200	8		15	225	100	800	* 9,1 / 10,7 m - 30/35 ft
250	10		15	225	100	1000	* 9,1 / 10,7 m - 30/35 ft
300	12		15	225	100	1200	* 9,1 / 10,7 m - 30/35 FEET

T-643 AA
"FLOWLINE E RISER" DI
PETROLIO GREGGIO 25 BAR



SOTTOSTRATO	NBR NERO
RINFORZO	CORDINE DI ACCIAIO AD ALTO CARICO
COPERTURA	CR NERO - RESISTENTE ALL'ABRASIONE, ALL'OZONO ED ALL'ACQUA DI MARE
APPLICAZIONE	"FLOWLINE AND RISER" DI PETROLIO GREGGIO PROGETTATO PER AGEVOLARE LE OPERAZIONI DI SROTOLAMENTO DALLA NAVE E POSA SUL FONDO MARINO. OTTIMA RESISTENZA A TRAZIONE. IDONEO PER USO CON RACCORDI DI SICUREZZA.
FATTORE SICUREZZA	4:1
TEMPERATURA	-30°C +93°C (-22°F +200°F)
MARCATURA	
TIPO MARCATURA	NON MARCATO
OMOLOGAZIONI	
NOTE	RESISTENZA A TRAZIONE: 102mm = 12.000 KG 152mm = 20.000 KG

Codice	DI mm	DI Inch	DE mm	Parete mm	Peso g/m	PE bar	PE PSI	Vuoto %	Raggio Curvatura mm	Lunghezza Disponibile m	Lunghezza Stock m
643AA102280000	102	4"	128	13	6740	25	375				
643AA152800000	152	6"	180	14	11300	25	375				